

EntroStar Panel

NATIVE BACNET TECHNOLOGY

The StarWatch SMS platform easily integrates with EntroStar™ access control panels, offering true open connectivity for diverse applications. Designed to communicate with any ANSI/ASHRAE 135-2010 compliant system, EntroStar PoE/PoE+ native BACnet® panels enable the merging of access control, security, and building management systems.

Each EntroStar controller supports two doors with combinations of magnetic locks and electric strikes/releases and up to four Wiegand compatible readers without the need for a local power supply¹. The panel can be installed directly or housed within a metal enclosure with an optional 15VDC power supply. The unit can also provide local battery back-up charged by the PoE/PoE+ supply.

KEY FEATURES

- Auto-discovery of panels across disparate networks
- Automatic issuance of IP addresses, static or DHCP
- Built upon standards-based BACnet protocol
- PoE/PoE+ design powers 2 locking devices and 4 readers, eliminating need for external power supply
- 4-state alarm monitoring
- Innovative status indication LEDs and icons reduce installation and configuration time



With innovative features for self-configuration and network discovery, EntroStar access control panels offer simple connection and interface to StarWatch SMS systems.

SIMPLIFIED INSTALLATION

EntroStar panels are specifically designed to facilitate ease of installation and configuration, typically cutting total deployment time in half. RJ45 jacks are used for door reader connections, allowing standard CAT5 FTP cabling for both readers and communications.

Innovative diagnostic LEDs allow complete local commissioning without the need for special tools or even a laptop. With the inclusion of rapid auto-discovery features for “plug and play” functionality, EntroStar technology signifies a paradigm shift in installation simplicity.

¹ current total not to exceed PoE/PoE+ specifications



STARWATCH™

SMS

FACILITIES

- Connects to 3rd-party BACnet compliant systems
- Powers 4 readers, 2 locks via PoE+
- Plug and play network connection
- Designed to UL 294 and 1076
- Up to 9 supervised inputs, 4 outputs
- Unique status indication system

TECHNICAL DATA

- Processor: 200 MHz ARM 9
- Memory: 32/64/128 MB RAM, 256 MB Flash
- Operating System: Linux
- Database: SQL Lite
- Auxiliary I/O: 3 inputs, 2 outputs

ENVIRONMENTAL

- Operating: -40 to +70°C
- Storage: -40 to +70°C
- Humidity: up to 93% non-condensing at 40°C
- EMC: BS EN 55022, BS EN 50082-1
- Dimensions: 8.5 in x 5.25 in

TECHNICAL SPECIFICATIONS

ELECTRICAL

- Supply:
 - PoE: 12.9W (min) 15.4W (max)
 - PoE+: 25.5W (min) 34.2W (max)
 - DC: 14V (+10%/-25%) 50W (max), note: DC input incorporates reverse polarity protection
- Power Available for External Equipment:
 - PoE: 7.2W (min) 9.6W (max) total
 - PoE+: 17.7W (min) 26.4W (max) total
 - DC: 45W (max) total
 - Note: each Output A/Output B pair is limited to 800mA (PoE/PoE+) and 1.5A (DC), each reader port is limited to 500mA @ 25°C derated to 300mA @ 70°C
- Battery:
 - Type: lead-acid
 - Voltage: 12V
 - Capacity: 7Ah (recommended)
 - Note: battery charge times extended when using a larger capacity battery, battery connection incorporates reverse polarity protection
- Outputs: Contact Rating: 2A 30VDC

ADDITIONAL FEATURES

- Micro SDHC card support
- USB 2.0 interface
- 128 bit encryption
- FIPS 201 compliant

©2015 DAQ Electronics, LLC. All rights reserved.

This literature is for guidance only. It does not constitute recommendations, representation, or advice, nor is it part of any contract. Our policy is one of continuous product improvement, and the right is reserved to modify the specifications contained herein without notice. All trademarks and names mentioned in this document are duly acknowledged.